

RD Certificate Number: EWWS645

Duratherm® OS spray applied polyurethane foam for stabilisation and insulation

Description

This is an assessment of Duratherm® OS spray applied HFC blown polyurethane foam for roof stabilisation and insulation. Applications assessed are stabilisation, insulation and insulation plus stabilisation.

Duratherm® OS is a 2 component modified polyurethane rigid foam system suitable for use in both flat and pitched roof applications. The material is formed in situ by mixing isocyanate and resin within the nozzle of a spray gun during the spraying process. The foam is spray applied in layers not exceeding 20mm with additional layers added to provide thickness. Curing of Duratherm takes place within 2 hours.

Scope of Registration

Due to space limitations, the Registered Detail certificate should be consulted for the full scope of this registration.



Validity

This system has been checked for compliance in accordance with English, Welsh and Scottish Building Regulations. LABC Warranty also accepts its use when installed and used in accordance with the Scope and Conditions of the Registered Details Certificate and in relation to LABC Warranty's current Technical Standards.

Registration was first issued on 01/06/16 and is valid until 01/06/20 providing there are no amendments to applicable regulations.

Issue dated 21/05/2019

Further Information

For more detailed information including access to the full certificate and supporting documents please use this link <https://www.labc.co.uk/business/labc-assured/ewws645-durathermr-os-spray-applied-polyurethane-foam-stabilisation-and-insulation>

Isothane Ltd

Newhouse Road

Huncoat Business Park

Accrington

Lancashire

BB5 6NT

Tel: 01254 872555

Email: richard.spencer@isothane.com

Web: www.isothane.com

